

**CAPACIDAD DE CARGA (A)
DE LOS CABLES DE COBRE**
Temperatura ambiente de 30°C

CALIBRE AWG O MCM	TEMPERATURA DE REGIMEN DEL CONDUCTOR					
	60°C	75°C	90°C	60°C	75°C	90°C
	TW	THW THWN XHHW* TTU	THHN XHHW** TTU	TW	THW THWN XHHW* TTU	THHN XHHW** TTU
	Cables monopolares al aire			Cables monopolares en Calibración ó Directamente Enterrados		
14	25	30	30	20	20	25
12	30	35	40	25	25	30
10	40	50	55	30	35	40
8	60	70	80	40	50	55
6	80	95	105	55	65	75
4	105	125	140	70	85	95
2	140	170	190	95	115	130
1	165	195	220	110	130	150
1/0	195	230	260	125	150	170
2/0	225	265	300	145	175	195
3/0	260	310	350	165	200	225
4/0	300	260	405	195	230	260
250	340	405	455	215	255	290
300	375	445	505	240	285	320
350	420	505	570	260	310	350
400	455	545	615	280	335	380
500	515	620	700	320	380	430
600	575	690	780	355	420	475
700	630	755	855	385	460	520
750	655	785	885	400	475	535
800	680	815	920	410	490	555
900	730	870	985	435	520	585
1000	780	935	1055	455	545	615

Notas:

* Aplicable a lugares húmedos

** Aplicable a lugares secos

No más de tres conductores en Canalización o cable